



# Eco-Promenade<sup>®</sup>



1-800-UNILOCK | [UNILOCK.COM](http://UNILOCK.COM)

**UNILOCK**  
PAVERS & WALLS



# ECO-PROMENADE®

ENDURACOLOR™ PERMEABLE



OPAL BLEND

Other finishes available: Il Campo®, Series™ & Umbriano®.



## PRODUCT ATTRIBUTES

Visual Appearance	Long, linear look and feel for any contemporary permeable application.
Finish	By special order, you may select from a variety of standard and architectural finishes; Premier ( <i>smooth</i> ), Il Campo® ( <i>brushed</i> ), Series™ ( <i>exposed aggregate</i> ) and Umbriano® ( <i>mottled</i> ).

## PRODUCT SPECIFICATIONS





2 $\frac{7}{8}$  x 12 x 4"  
75 x 300 x 100mm

### EDGE DETAIL



ROUNDED EDGE

## LAYING PATTERNS



## RECOMMENDED SAND



### Gator Aqua Rock

- For Residential & Commercial applications
- For permeable paver joints
- Helps prevent erosion due to climatic conditions
- Use as bedding and jointing material
- Graded to meet ASTM No. 9 water rate
- Long term high infiltration performance
- 2,200 lb Supercrack available for large applications

### Coverage:

Size	Area
50lb. bag	20-25 sqft
2,200 lb. Super Sack	880-1100 sqft

(Based on 60mm paver.)

## PERMEABLE PAVEMENT DATA

Small: 1/4" Joint					MIN. INFILTRATION RATE FOR RAINFALL OF:			
	JOINT MATERIAL	JOINT WIDTH*	VOID SPACE*	SURFACE INFILTRATION RATE**	2" / HR	4.5" / HR	6.5" / HR	11" / HR
	ASTM #9 SEK Chip	7 MM	10.12%	934" / HR	20	44	64	109

\*Joint Width is measured at the top of the paver. Void Space is calculated at the base of the paver. \*\*Infiltration rate is based on testing done when first installed and is an approximate. Permeable spacers are available for use with extended range of Unilock products.

## TECHNICAL INFORMATION

### ASTM C 936 Standard Specifications for Solid Concrete Interlocking Paving Units

Conforms to:

- C140 for Absorption 5% avg - 7% max
- Compressive Strength > 7,200 PSI avg.
- C67 for Freeze-thaw Durability
- C418 for Abrasion Durability
- Dimensional Accuracy **+/- 3 mm**

Test results available upon request

### Meets the U.S. Architectural & Transportation Barrier Compliance Board Slip-Resistance Surfaces Advisory Guidelines

## TECHNICAL ADVANTAGES

### ENDURACOLOR™

Refined surface and long-lasting colour

### PERMEABLE



Can be installed to allow water to flow through

## PRODUCT DATA


Stones & Bundling	Unit	SqFt Per				Per Bundle		Soldier LnFt Per			Sailor LnFt per			Units Per			Lbs Per		
	Thickness	Bundle	Layer	Section	Stone	Layers	Sections	Unit	Section	Bundle	Unit	Section	Bundle	SqFt	Section	Bundle	Layer	Section	Bundle
Georgetown Manufacturing																			
3" x 12" Permeable	4" (100mm)	53.28	10.66		0.24	5	-	0.92	-	57.7	0.25	-	216.50	4.13	-	220	488	-	2,439

Notes: **Sold in full bundles only and is produced and sold on a required, refundable skid.** Custom finish and color options are available. **Special order - lead time is required.** Minimum quantities apply. \*Weights vary depending on plant of manufacture & finish. **Important: A urethane rubber paver mat must be used to prevent scuffing.** For permeable installations, Unilock recommends using granite chips for joint filler. All measurements are nominal. Contact your Unilock Territory Manager or call 1-800-UNILOCK for further information. \*For custom options, please contact your Unilock Territory Manager.

## APPLICATIONS



## SOLAR REFLECTIVE INDEX (SRI) TESTING DETAILS

Product	Solar Reflectance	SRI
Opal Blend	0.32	34 

## LEED INFORMATION

### Materials & Resources: LEED V4:

Building Product Disclosure and Optimization

Sourcing of Raw Materials - Sourcing of Raw Materials and Extraction • **1 point**

Sourcing of Raw Materials - Leadership Extraction Practices • **1 point**

Material Ingredient Reporting - Material Ingredient Reporting • **1 point**

Material Ingredient Reporting - Material Ingredient Optimization • **1 point**

Environmental Product Declaration • **1 point**